

Dromex



LADIES D59 FLAME & ACID SUIT



DWL-D59FA

Description

Dromex® Ladies D59 flame and acid treated jacket and pants are designed to protect the user from the hazards of accidental flame contact and acid splashes reducing injury when working in hazardous environments.

The Dromex® DWL-D59FA pants and jacket is approved to the latest SANS 434 specification and has the SABS permit marking.

The D59 drill fabric construction is heavy duty and durable whilst the flame acid garment treatment technology resists the effects of flame contact and acid corrosion offering the user essential protection in the workplace.

The 100% cotton satin weave finish and natural fibre construction makes this garment comfortable and breathable.

This garment consists of the following:

Jacket features:

- Collared jacket with internal hanger loop.
- High visibility flame retardant reflective tape on arms for enhanced visibility when working in poor lighting environments.
- Concealed brass YKK zip closure.
- 2 Open waist pockets and 1 left breast pocket with a Dromex® side-winder label and mitred flap with concealed metal press stud closure.
- Bust darts for better fit.
- Side slits for comfortable fit over waist.
- Elasticated sleeve cuffs prevents the risk of loose clothing caught in machinery.
- Seams with triple needle topstitching for added durability.
- Flame retardant and acid resistant embroidery on arm for garment identification.

Pants features:

- All seams with triple needle topstitching for durability.
- Flame retardant reflective tape on leg for enhanced visibility when working in poor lighting environments.
- A concealed brass YKK zip and with metal nickel button closure at waist.
- Two fronts swing pockets and a rear mitred open pocket.
- A tool pocket on the right leg.
- A Dromex® sidewinder label on back pocket.
- An inner elasticated waist for optimum fit and flexibility with belt loops.

This garment is suitable for use in general work environments such as engineering, smelting operations, mining, construction, oil and gas, petroleum, maintenance, repairs and welding industries.

Special Instructions

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection. These flame and acid garments are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment therefore it is the responsibility of the end user and not the manufacturer or supplier to determine the garment suitability for the intended use. Flame and acid protective garments should be thoroughly inspected before use to ensure no damage is present.

Should there be visible damage such as tears or burn holes, it is recommended to replace the garment immediately.

Specifications

Style:	Navy blue, ladies cut pants and jacket with high visibility reflective tape on arms and legs.
Fabric composition:	100% Cotton.
Mass:	320gsm.
Reflective:	50mm Silver flame retardant tape.

Compliance & Conformity

- Garments comply to the latest SANS 434 standard (This standard specifies requirements for the material, cut, make and trim of boiler suits, two-piece work wear suits, bib and brace overalls, coats and unlined jackets).

This standard makes reference to the following relevant standards:

SANS 1362	Sewing threads.
SANS 1387-4	Part 4: Cotton jean and drill fabrics.
SANS 1387-10	Part 10: Pocketing.
SANS 1822	Slide fasteners.
SANS 5278	Sewing stitches per unit length.
SANS 10235	Fibre-content labelling of textiles and textile products.
SANS 50471	High-visibility warning clothing for professional use.

- The fabric is to SANS 1387-4 for D59 drill fabric, 4/1 satin weave @270gsm, 37 thread per cm weft and 19 threads per cm warp. The breaking strength is 940 N warp and 510 N weft.

• Flame retardant fabric is tested to SANS 1423-1 for textile fabrics of low flammability for apparel:

Class B Category 1:

The fabric ignites within a given time period and might continue to flame but at a rate of flame propagation that is within a specified limit. Surface Flash None.

Ignition time (seconds) _ 20 sec.

Rate of flame propagation 5 mm/s.

** Note this is a test situation for the fabric and does not cancel or imply otherwise to the labels wash instruction.

• Flame retardant silver retro-reflective tape is tested to SANS 50471:2006 (EN 471:2003 + A1:2008) and SANS 1423-1:2008 for textile fabrics of low flammability for apparel:

High visibility warning protective clothing capable of signalling the users presence visually, intended to provide conspicuity of the user in hazardous situations under any light conditions by day and under illumination by vehicle headlights in the dark. Performance requirements are included for retro-reflection and not for the entire garment.

• Acid resistant fabric is tested to ISO 6530:2005 for protection against liquid chemicals:

Two levels of the potential performance are assessed by this method of testing to meet with possible requirements for protection against:

- a) Deposition on the surface of a material, at minimal pressure, of spray droplets up to coalescence or occasional small drips.
- b) Contamination by a single low-volume splash or low-pressure jet allowing sufficient time to divest the clothing or take other action as necessary to eliminate any hazard to the wearer from chemical retained by the protective garment or in circumstances where pressure is applied to liquid contaminants on the surface of the clothing material, as a result of natural of the wearer (flexing of contaminated areas of clothing at arms, knees, shoulders) and contact with contaminated surfaces (e.g. walking through sprayed foliage).

Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa
T. +27(31) 713 1960 E. info@dromex.co.za

www.dromex.co.za

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 11/11/2021

Acid resistance for protective clothing against liquid chemicals for performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals. The acid resistant finish is primarily a liquid proof coating that is not destroyed by the action of acids or other chemicals. It doesn't allow the cloth to be wetted by the acids and is therefore "acid resistant":

The test chemicals are:

- Hydrochloric Acid (HCl) 32%
- Sulphuric Acid (H₂SO₄) 24%
- Nitric Acid (HNO₃) 65%
- Sodium Hydroxide (NaOH) 40%

There is no SANS specification for Acid Resistance therefore alternate testing is done in the absence of a national standard. The tests are done to the ISO 6530:2005 and the chemical selection and concentration to the withdrawn DIN32763 standard.

Packaging, Storage & Obsolescence

Dromex® DWL-D59FA-J - jackets are packed in individual polybags and sold as 20 units per carton.
Dromex® DWL-D59FA-P - pants are packed in individual polybags and sold as 20 units per carton.

Cleaning & Maintenance

- The following suggestions will help keep your garment safe and neat:
- D59 garments can be cleaned by home cleaning or commercial laundering provided all the recommended conditions and settings are adhered to.
- Should home procedures not remove contaminants, then dry cleaning is recommended.
- Our recommended cleaning for these garments is as follows:
 - Flame Retardant garments should not be washed with personal non-flame retardant clothing to avoid contamination by flammable materials.
 - Pre-treat greasy stains and wash the garment in warm water with a light cleaning solvent.
 - Do not use Hypochlorite bleach or detergents containing Hypochlorite bleach as fading may occur.
 - Do not tumble dry.
 - Thoroughly rinse the garment to remove any wetting agents.
 - Do not hang in direct sunlight as fading may occur.
 - Iron the garment to enhance and re-generate the finish effect
 - When using commercial laundry aids, be sure to read and carefully follow the manufacturer's instructions.



- Note:
The flame-retardant finish is a permanent finish applied to the cotton fabric which reacts with the cotton fibre to produce a permanent covalent bond.

This is used internationally to produce a wash fast flame-retardant finish that lasts at least 50 washes.

WARNING:

Acid resistant garments when wetted with an acid and allowed to dry or stand in it's wetted state for a long period will destroy the fabric and holes will become visible and widen after each wash.

- Should acids wet the garment, it should be neutralised and washed as soon as practically possible.
- The chemical used in the acid finish is a Fluorocarbon and is permanent therefore should not lose its effect after 50 washes.

Sizes Available

Jacket:

Size designation	Nominal measurements of finished garment (cm)							
	Bust circumference	Hem circumference	Back length	Back width	Sleeve length	Shoulder	Cuff circumference relaxed	Cuff circumference stretched
S 34/87	107	107	74	42	50	17	17	27
M 38/97	117	117	75	45	51	17.5	18	28
L 42/107	127	127	76	48	52	18	19	29
XL 46/117	137	137	76	51	53	18.5	19	29
2XL 50/127	147	147	77	54	54	19	20	30
3XL 54/137	157	157	77	57	55	19.5	20	30
4XL 58/147	167	167	78	60	56	20	21	31
5XL 62/157	177	177	78	63	57	20.5	21	31

NOTE This information is for guidance only

Based, in accordance with SANS 1360-1, on the bust girth, in centimetres, of the intended wearer.

Pants:


Size designation	Nominal measurements of finished garment (cm)							
	Waist		Hip circumference	Back rise (excluding waistband)	Front (excluding waistband)	Outleg	Inleg	Bottom circumference
	Relaxed (min.)	Extended						
S 30/77	73	87	110	41	30	110	79	44
M 34/87	83	97	120	42	31	110	79	46
L 38/97	93	107	130	43	32	112	79	48
XL 42/107	103	117	140	44	33	113	79	49
2XL 46/117	113	127	150	45	34	114	79	50
3XL 50/127	123	137	160	46	35	115	79	50
4XL 54/132	133	147	170	47	36	116	79	51
5XL 58/147	143	157	180	48	37	117	79	51

NOTE This information is for guidance only

Based, in accordance with SANS 1360-1, on the waist girth and hip girth, in centimetres, of the intended wearer for example, 87/112 to fit waist 87cm and hip 112cm.


Marking

DROMEX




- Position:
- Jacket-Neck (Inside)
 - Pants-Left pocket (Inside)

SIZE



- Position:
- Jacket-Neck
 - Pants-Inside (left pocket-below main label)

SIDEWINDER



- Position:
- Jacket-Top pocket
 - Pants-Back (Right pocket)

Disposal


All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Please consider recycling.

EMBROIDERY FR & RESISTANT



- Position:
- Jacket - Right arm (Centre of panel)
 - Pants - Front (Right leg)

PRODUCT & YOM LABEL



- Position:
- Jacket-Neck (Below main label)
 - Pants-Inside (left pocket-below main label)

PRODUCT STANDARD



SANS 1387-4, SANS 1423-1, SANS 434:2018 Ladies cut, ISO 6530: 2005

Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa
T. +27(31) 713 1960 E. info@dromex.co.za

www.dromex.co.za

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 11/11/2021